



SEALTEK PTY LTD

ADVANCED COATING TECHNOLOGIES

44 Sophia Street, Fairlands, Johannesburg
 P.O. BOX 731 074, Fairlands 2030, South Africa
 TELEPHONE: + 27 10 594 - 4726
 E-mail: info@sealtek.co.za
 Reg no: 2015/358427/07

SPEC SHEETS - HYDROBLOCK

An Eco Friendly Pure Acrylic Waterproof Coating, which is adhesion promoted, UV Stable, flexible and extremely durable. Our waterproof coating is easy to apply and ideal for most waterproofing applications – Slabs, Roofs, and Foundations etc.

<p>Surface Preparation</p>	<ul style="list-style-type: none"> • Ensure that the Substrate has been washed off and is free of any dust or any objects and chemicals that might cause non-adhesion to the substrate. • Ensure that the substrate has dried properly before any application of the product.
<p>Method of Application</p>	<ul style="list-style-type: none"> • HydroBlock is pre-packaged in a 20ltr bucket – open bucket mix thoroughly at medium speed before application • Ensure the substrate has been properly prepared as above • Cover all surrounding and non-spray able areas with masking tape to avoid damage or overspray. • The final required thickness is 2000 micron(2mm) for Waterproofing purposes – Approximately 4-5coats depending on application method used. • Airless Spray application – Spray on the first layer of paint. Once the 1st coat is touch dry, apply the 2nd Coat and then a 3rd Coat. A flash coat can be applied afterwards if needed. • Roll on application – Roll on the first layer of paint reasonably thick. Once the 1st coat is touch dry apply a further 4-5 Coats after each coat is touch dry. This is to ensure that the waterproofing has been applied to the required thickness. • Brush on application - Brush on the first layer of paint reasonably thick. Once the 1st coat is touch dry apply a further 4-5 Coats after each coat is touch dry. This is to ensure that the waterproofing has been applied to the required thickness
<p>Practical Coverage</p>	<ul style="list-style-type: none"> • 25 m² per 20ltr bucket at a 4-5 coat application
<p>Cleaning</p>	<ul style="list-style-type: none"> • Our Paint is water based therefore paint and application tools can be cleaned off with running water.
<p>Drying Time</p>	<ul style="list-style-type: none"> • Touch Dry or before another coat – 1-2 Hours at ± 25 °C • Fully Cured - 7 Days at ± 25 °C
<p>Colours</p>	<ul style="list-style-type: none"> • Standard colours for waterproofing are Grey, White, Black, Terra Cotta and Green. We can however supply the waterproofing in any of our 90 standard colours or some colours can be matched on request