



SEALTEK PTY LTD

ADVANCED COATING TECHNOLOGIES

44 Sophia Street, Fairlands, Johannesburg
P.O. BOX 731 074, Fairlands 2030, South Africa
TELEPHONE: + 27 10 594 - 4726
E-mail: info@sealtek.co.za
Reg no: 2015/358427/07

SPEC SHEETS - AQUATINT

AquaTint is a Polymeric additive mixture that has excellent saturation levels that enhances the stability of the substrate. It also repels water from the substrate. This makes for the ideal finish on a slab where you want a colour finish over our PolyScreed. Used on a variety of substrates, such as concrete, walls, plaster, tiles, etc.

Surface Preparation	• Ensure that the Substrate has been washed off and is free of any dust or any objects and chemicals that might cause non-adhesion to the substrate. • Ensure that the substrate has dried properly before any application of the product.
Method of Application	• AquaTint is pre-packaged in a 20ltr bucket – open bucket mix thoroughly at medium speed before application • Ensure the substrate has been properly prepared as above • Cover all surrounding and non-spray able areas with masking tape to avoid damage or overspray. • Airless Spray application – Spray on one layer of AquaTint. • Roll on application – Roll on two thin layer of AquaTint. Roll on the AquaTint in one direction only. • Brush on application - Brush on two thin layers of AquaTint. Brush on AquaTint in one direction only.
Practical Coverage	• 100-120 m² per 20ltr bucket at coat application
Cleaning	• AquaTint is water based therefore paint and application tools can be cleaned off with running water.
Drying Time	• Touch Dry or before another coat ± 1 Hour at ± 25 °C
Colours	• Depend on the colour chosen , we have a variety of 90 standard Colours.