



SEALTEK PTY LTD

ADVANCED COATING TECHNOLOGIES

44 Sophia Street, Fairlands, Johannesburg
P.O. BOX 731 074, Fairlands 2030, South Africa
TELEPHONE: + 27 10 594 - 4726
E-mail: info@sealtek.co.za
Reg no: 2015/358427/07

SPEC SHEETS - REPELLAM

Repellam is a Polymeric additive mixture that has excellent saturation levels that enhances the stability of the substrate. It also repels water from the substrate. This makes for the ideal primer and bonding agent for most applications. Used on a variety of substrates, such as concrete, walls, plaster, tiles, etc.

Surface Preparation	<ul style="list-style-type: none">• Ensure that the Substrate has been washed off and is free of any dust or any objects and chemicals that might cause non-adhesion to the substrate.• Ensure that the substrate has dried properly before any application of the product.
Method of Application	<ul style="list-style-type: none">• Repellam is pre-packaged in a 20ltr bucket – open bucket mix thoroughly at medium speed before application• Ensure the substrate has been properly prepared as above• Cover all surrounding and non-spray able areas with masking tape to avoid damage or overspray.• Airless Spray application – Spray on one layer of Repellam.• Roll on application – Roll on one thin layer of Repellam. Roll on the Repellam in one direction only.• Brush on application - Brush on one thin layer of Repellam. Brush on Repellam in one direction only.
Practical Coverage	<ul style="list-style-type: none">• 120 m² per 20ltr bucket at 1 coat application
Cleaning	<ul style="list-style-type: none">• Repellam is water based therefore paint and application tools can be cleaned off with running water.
Drying Time	<ul style="list-style-type: none">• Touch Dry or before another coat ± 1 Hour at ± 25 °C
Colours	<ul style="list-style-type: none">• Clear when dry