



# SEALTEK PTY LTD

## ADVANCED COATING TECHNOLOGIES

44 Sophia Street, Fairlands, Johannesburg  
 P.O. BOX 731 074, Fairlands 2030, South Africa  
 TELEPHONE: + 27 10 594 - 4726  
 E-mail: info@sealtek.co.za  
 Reg no: 2015/358427/07

### SPEC SHEETS - ROOFRENEW

An Eco Friendly Acrylic roof paint. RoofRenew is a water-based Lead free paint which is adhesion promoted, UV Stable and extremely durable. This makes for the ideal coating to rejuvenate your roof.

Surface Preparation	<ul style="list-style-type: none"> <li>• Ensure that the Substrate has been washed off and is free of any dust or any objects and chemicals that might cause non-adhesion to the substrate.</li> <li>• Ensure that the substrate has dried properly before any application of the product.</li> </ul>
Method of Application	<ul style="list-style-type: none"> <li>• RoofRenew is pre-packaged in a 20ltr bucket – open bucket mix thoroughly at medium speed before application</li> <li>• Ensure the substrate has been properly prepared as above</li> <li>• Cover all surrounding and non-spray able areas with masking tape to avoid damage or overspray.</li> <li>• Airless Spray application – Spray on the first layer of paint. Once the coat is touch dry, a Flash coat can be sprayed on if needed.</li> <li>• Roll on application – Roll on the first layer of paint. Once the 1<sup>st</sup> coat is touch dry one can do the 2<sup>nd</sup> coat, a 3<sup>rd</sup> flash coat can be applied if needed.</li> <li>• Brush on application – Brush on the first layer of paint. Once the 1<sup>st</sup> coat is touch dry one can do the 2<sup>nd</sup> coat, a 3<sup>rd</sup> coat can be applied if needed.</li> </ul>
Practical Coverage	<ul style="list-style-type: none"> <li>• 60m<sup>2</sup> per 20ltr bucket on a 2-3 coat application</li> </ul>
Cleaning	<ul style="list-style-type: none"> <li>• Our Paint is water based therefore paint and application tools can be cleaned off with running water.</li> </ul>
Drying Time	<ul style="list-style-type: none"> <li>• Touch Dry or before another coat – 1-2 Hours at ± 25 °C</li> <li>• Fully Cured - 7 Days at ± 25 °C</li> </ul>
Colours	<ul style="list-style-type: none"> <li>• Standard colours for waterproofing are Grey, White, Black, Terra Cotta and Green. We can however supply the waterproofing in any of our 90 standard colours or some colours can be matched on request</li> </ul>